

LOBADUR® HS GlobaSeal

Special low solvent based primer for parquet and hardwood floors for a clear color reinforcement under LOBADUR® Water Based Finishes.

Article No.: 11030
Gloss Level: n/a
Package Size: 3l, 1l
Giscode: Ö40
Solids: Ca. 90%
Viscosity DIN 4: Not defined

Range of Use: Parquet and hardwood floors of european and tropical types of wood. Please note the LOBA list of wood types. When in doubt ask the factory.
Clear color reinforcement
The side bonding effect will be decreased.
Oxidativ drying

Information on Use:

- Shake material well
- Use a stainless finish trowel
- Work with a single disc grinder and the LOBATool Normal Pad beige.
- Work in sections
- Alternatively (dark colour wood) coat with LOBATool Roller Microfaser 60 – 80 as thin as possible, wait about 1 Hour and work with a single disc in the same way
- After completing a room repeat the procedure with the LOBATool Normal Pad green until the surface appears evenly satin.
- Clean dirty tools (pads, wiper, paper, towels, etc.) with water and let them dry outside. – SELF INFLAMMABLE!

Setup Recommendations:
Parquett and Hardwood Floors:

1. Prepare surface and apply LOBADUR® HS GlobaSeal sectionally.
2. Use the LOBATool normal pad (beige) until all excess is gone.
3. Repeat the procedure with the LOBATool normal pad (green).
4. Drying
5. Roll LOBADUR® waterbased Finish onto surface.

Covering Tools: LOBATool Roller Mikrofaser 60-80 LOBATool stainless trowel
LOBATool normal pad beige and LOBATool normal pad green

Covering Quantity: Roller ca. 40 – 50 ml/m² (4 – 5 ml/square foot) Trowel: 20 - 40 ml/m² (2 – 5 ml / square foot)

Drying Time: Able to re-apply finish after at least 12 hours, drying over night.
When delay in drying, please wait until the surface is completely dry.

Suitable Finishes for Recoating: **Up to heavy wear** **Up to extremely heavy wear**
LOBADUR® WS Global LOBADUR® WS 2K Supra
LOBADUR® WS Viva LOBADUR® WS 2K Duo

Intermediate Sanding: Do not intermediate sand LOBADUR® HS GlobaSeal.

Thinner: The material is ready-to-use and cannot be diluted!

Cleaning of Tools: Immediately clean with LOBADUR® KH Thinner or LOBADUR® Universal Cleaner.

Storage and Transportation: Store in a cool and dry place; not sensitive to frost; storable for 12 months; not a hazardous material according to ADR, dirty tools are self inflammable!

The General Information on the Use of LOBADUR® WS Products are part of this Information and must be noticed.

LOBA GmbH & Co. KG
Tel: +49 (0) 7156 357 220
Fax: + 49 (0) 7156 357 211
Mail: service@loba.de

revised:03.04.2008 DK