

LOBADUR® WS Exotengrund

Waterborne primer for roller application based on acrylate-resins for parquet and hardwood floors. Excellent locking effect against wood dye and other wood contents.

Article No.:	11495	2004/42/CE
Gloss Level:	n/a	EU limit value fort this product
Package Size:	5l,	(cat. A/i): 140g/l (2007/2010)
Giscode:	W2 / substitute product according to TRGS 617	This product contains max 32g/l VOC
Solids:	11 ± 1%	
Viscosity DIN 4:	11 ± 1s	

Range of Use: Parquet and hardwood floors of tropical types of wood aswell as smoked oak. Check the LOBA list of different types of wood. When in doubt check with the technical department. Reduces side-bonding effect of waterborne finishes. Impregnating, non layer building.

Information on Use:

- Shake material well
- Do not put material directly on the floor, use a LOBATool sealing bucket.

Setup Recommendations:

1. Prepare surface and apply a thin coat of LOBADUR® WS Exotengrund using a roller
2. Drying
3. Roll LOBADUR® waterbased finish onto surface

Parquet and Hardwood Floors:

Covering Tool: LOBATool roller Universal 100 or LOBATool roller Microfaser 60 - 80

Covering Quantity: Roller application 80 - 100 ml/m² (10 - 12m²/l), 8 – 10 ml / square foot

Drying Time: Earliest possible recoating after ca. 2 hours
If there is a delay in drying, wait until you can see that the surface is completely dry.

Suitable Finishes for Recoating:	Normal wear	Up to heavy wear
	LOBADUR® WS Life	LOBADUR® WS Viva LOBADUR® WS Global LOBADUR® WS EasyFinish
	Up to extremely heavy wear	Sportsfloors of tropical types of wood
	LOBADUR® WS 2K Supra LOBADUR® WS 2K Duo	LOBADUR® WS SportFinish LOBADUR® WS 2K SportExtreme

Intermediate Sanding: Do not intermediate sand LOBADUR® WS Exotengrund.

Thinner: The primer is ready-to-use and cannot be diluted!

Storage and Transportation: +5 to + 25°C (41 °F to 77°F) , storable for 12 months, not a hazardous material according to ADR

The general Information on the Use of LOBADUR® WS Products are part of this Information and must be noticed.

LOBA GmbH & Co. KG
Tel: +49 (0) 7156 357 169
Fax: + 49 (0) 7156 357 211
Mail: service@loba.de